

HAMPTON

Hampton Controls

1-800-437-2664

www.hamptoncontrols.com

DURAKOOL Series 60APS 60 Amps

2 POLE

The Durakool 60 Amp high performance contactor (normally open) is designed for resistive loads typical in industrial ovens, food processing and laboratory equipment, lighting and computer power supplies, plus medical and communications equipment.

The 60 Amp contactor is UL/CSA listed for general purpose, inductive, and tungsten, as well as resistive loads. The contactor features long life, quiet operation, and rapid on/off cycling. Since it is hermetically sealed, it is a practical replacement, especially in hostile environments.

SPECIFICATIONS

Maximum Time:	Operate 70 ms, Max.	Release 90 ms, Max
Contact Bounce:	None	
Recommended DC Load Polarity:	Top Connection Negative	
Breakdown Voltage:	2000 VRMS/Min.	
Contact to Contact:	5000 VRMS/Min.	
Contact to Ground:	5000 VRMS/Min.	



TYPE/SERIES		60APS 60 Amps		Typical Coil Data			
DESCRIPTION		Part Number	DC Ohms	Watts	Amps	V.A.	
2 Pole (Normally Open)	Volts 24	2060APS24AC	15	5.20	0.525	12.60	
	120	2060APS120AC	350	7.46	0.133	15.96	
	240	2060APS240AC	1520	6.18	0.056	13.44	
	480	2060APS480AC	5600	6.47	0.027	12.96	
	12 (DC)	2060APS12DC	24	6.10	0.506	6.07	
	24 (DC)	2060APS24DC	90	6.00	0.253	6.07	

ELECTRICAL RATINGS	60 Hz					DC		
	Volts	120	208	240	277	480	48	120
Resistive		60	60	60	60	60	60	30
General Purpose		60	60	60	60	60	—	—
Tungsten (1 Pole)		60	60	60	60	35	60	30
Motor Load								
1 Phase (Hp)		3.0	3.0	5.0	5.0	7.5	—	—
3 Phase (Hp)		5.0	5.0	10.0	10.0	15.0	—	—

HAMPTON

Hampton Controls

1-800-437-2664

www.hamptoncontrols.com

DURAKOOL Series 60APS 60 Amps

2 POLE

