

HAMPTON

Hampton Controls

1-800-437-2664

www.hamptoncontrols.com



High Voltage Contactors (2500-3500 Volts at 10 Amps AC & 4000 Volts at 8 Amps AC)

With 10 Amp ratings and several standard options, Durakool high voltage contactors are a versatile choice for UV curing lamp controls and panel safety switching and other high voltage loads. The 2500 VAC or 3500 VAC rated models, single-pole are made either normally open or normally closed. Terminals come with standard pressure connectors or 5000 VAC rated leads. HV contactors are compact for easy panel mounting, and provide mercury switching dependability.

SPECIFICATIONS

Maximum Time:	Operate	Release
Normally Open	90 ms, Max.	140 ms, Max.
Normally Closed	200 ms, Max.	100 ms, Max.
Contact Bounce, Release:	Allowed on normally open models	
Recommended DC Load Polarity:	Top Connection Negative	
Load Connectors:	Pressure Connector #1-18 AWG Cu.	
Coil Terminals:	#6-32 Wire Binding Screw, Max. #12 AWG Cu.	
Breakdown Voltage:	500 VRMS/Min. Across Contacts	
Weight:	1.5 lbs.	



TYPE/SERIES	Normally Open		
DESCRIPTION	Part Number	Typical Coil Data	
		Hz DC Ohms Watts Amps	
2500 Terminal	Volts		
	120	CFH-302	50/60 180 9.0 0.174
	240	CFH-303	50/60 680 9.3 0.089
2500 Black Leads	120	CFH-216	50/60 180 9.0 0.174
	240	CFH-215	50/60 680 9.3 0.089
	24 (DC)	CFH-226	— 111 5.2 0.217
	48 (DC)	CFH-238	— 440 4.8 0.100
3500 Terminal & 4000 Terminal	120	CFCH-397 & CFCH-418	50/60 180 9.0 0.174
	240	CFCH-387 & CFCH-419	50/60 680 9.3 0.089
	24 (DC)	CFCH-396 & CFCH-420	— 111 5.2 0.217
	Normally Closed		
2500 Terminal	120	CBH-302	60 180 8.5 0.179
	120	CBH-305	50 180 9.8 0.196
	240	CBH-303	60 680 9.3 0.093
2500 Black Leads	120	CBH-225	50 180 9.8 0.196
	120	CBH-218	60 180 8.5 0.179
	240	CBH-222	50 680 9.3 0.089
	240	CBH-215	60 680 9.3 0.093
	24 (DC)	CBH-221	60 111 5.2 0.217
3500 Terminal	120	CBCH-333	50/60 180 8.5 0.179
	210	CBCH-337	50/60 600 7.4 0.086
	240	CBCH-335	60 680 9.3 0.093
	48 (DC)	CBCH-339	— 440 4.8 0.100

